


SERİ	MODEL	GÖRSEL	AÇIKLAMA	FİYAT
ZEPHYR MIXER	ZEPHYR ZMX52		5-CHANNEL COMPACT MIXER 8 total inputs including an XLR jack with phantom power and EQ on channel one Two stereo input channels with balanced TRS jacks http://altoproaudio.com	\$122,00
	ZEPHYR ZMX862		6-CHANNEL COMPACT MIXER 8 total inputs including an XLR jack with phantom power and On channels one and two And balanced line inputs Three-shelf EQ on each mono and stereo channel http://altoproaudio.com	\$193,00
	ZEPHYR ZMX124FXU		12 CHANNEL MIXER WITH EFFECTS USB INTERFACE 20 total inputs including XLR jacks with phantom power on channels 3-band EQ with swept mid on microphone channels 4-band fixed EQ on stereo line channels Stereo 9-band graphic EQ 4 AUX sends per channel: 2 PRE/POST faders switchable 4-bus sub mixer 60mm high precision faders 256 24-bit ALESIS DSP effects (16 presets x 16 variations) USB audio interface for computer software recording and monitoring http://altoproaudio.com	\$850,00
	ZEPHYR ZMX164FXU		16 CHANNEL MIXER WITH EFFECTS USB INTERFACE 28 total inputs including XLR jacks with phantom power on channels 3-band EQ with swept mid on microphone channels 4-band fixed EQ on stereo line channels Stereo 9-band graphic EQ 4 AUX sends per channel: 2 PRE/POST faders switchable 4-bus sub mixer 60mm high precision faders 256 24-bit ALESIS DSP effects (16 presets x 16 variations) USB audio interface for computer software recording and monitoring http://altoproaudio.com	\$984,00
EMPIRE POWERED MIXER	EMPIRE TMX80 DFX		8 CHANNEL POWERED MIXER 14 Total inputs including 4 XLR jacks with phantom power 1400W PEAK POWER 2x350W @ 4 ohm / 2x180W @ 8 ohm Class D Power 48V Phantom Power On-board ALESIS digital effects processor http://altoproaudio.com	\$904,00
	EMPIRE TMX120 DFX		12 CHANNEL POWERED MIXER 22 Total inputs including 8 XLR jacks with phantom power 1400W PEAK POWER 2x500W @4 ohm / 1000W @ 8 ohm Bridged Class D Power 48V Phantom Power On-board ALESIS digital effects processor http://altoproaudio.com	\$1.440,00
	EMPIRE TMX160 DFX		16 CHANNEL POWERED MIXER 30 Total inputs including 12 XLR jacks with phantom power 2x750W @4 ohm / 1500W @ 8 ohm Bridged Class D Power 48V Phantom Power On-board ALESIS digital effects processor http://altoproaudio.com	\$1.640,00
	EMPIRE TMX200 DFX		20 CHANNEL POWERED MIXER 38 Total inputs including 16 XLR jacks with phantom power Tabletop 20 Channel Powered Mixer with 24-Bit DSP FX 2x750W @4ohm(RMS) + 2x500W @4ohm(RMS) 1500W @ 8ohm Bridged + 1000w @ 8ohm Bridged Class D Powers 48V Phantom Power On-board ALESIS digital effects processor http://altoproaudio.com	\$2.368,00
	EMPIRE RMX1008 DFX		1000W POWERED CABINET MIXER WITH EFFECTS 18 total inputs including 8 XLR jacks with phantom power 1000 Watts @ 8 ohm Bridged Cabinet Style 24-Bit DSP FX, Dijital Effect Processor 3-Shelf Graphic EQ 2x500W @4 ohm(RMS) Class D Digital Power On-board ALESIS effects processor http://altoproaudio.com	\$1.070,00
LINE ARRAY	SXA18P		18" VENTED LINE ARRAY SUBWOOFER Power System: 750W conts./ 1500W Program/3000W Peak Operating Frequency Range (-10 dB): 37 Hz - 200 Hz Frequency Response (-3 dB): 43 Hz - 200 Hz Nominal SPL @ 1m: 122dB SPL Continuous (Direct Mode) Maximum SPL @ 1m: 125 dB Peak (Direct Mode), 122 dB SPL Continuous (Direct Mode) http://altoproaudio.com	\$1.740,00
	SXA28P		PROFESSIONAL 2 WAY LINE ARRAY LOUD SPEAKER 2x8" LF+2x1" HF Power System: 400W conts./ 800W Program/1600W Peak Operating Frequency Range: (-10dB): 65 Hz - 20 kHz Frequency Response (-3dB): 77 Hz - 18 kHz Maximum SPL @ 1m: 125 dB Peak (Passive Mde), 122 dB SPL Continuous (Passive Mode)	\$2.600,00
	TRUESONIC TS112		12" 2 WAY PASSIVE Speaker Power System: 200W continius/400W Program/800W Peak Frequency Response (-10dB): 52 Hz-18 kHz Sensitivity (1w @ 1mt): 96 dB SPL Impedance: 8 ohms (nominal) Maximum SPL @ 1m: 119 dB continuous / 127 dB peak http://altoproaudio.com	\$470,00

PASSIVE SPEAKER SYSTEM		<p>15" 2 WAY PASSIVE Speaker Power System: 250W continius/ 500W Program/1000W Peak Frequency Response (-10dB): 48 Hz-18 KHz Sensitivity (1w @ 1mt): 97 dB SPL Impedance: 8 ohms (nominal) Maximum SPL @ 1m: 121 dB continuous/ 127 dB peak http://altoproaudio.com</p>	\$536,00
		<p>12" 2 WAY PASSIVE Speaker Power System: 200W continius/ 400W Program/800W Peak Max SPL at 1m: 119 dB Program / 122 dB Peak Frequency Response (-10dB): 65 Hz-20 KHz Impedance: 8 Ohms Nominal Crossover Frequency: 2.5 kHz /12 dB / Octave 15mm PAINTED BIRCH PLY CABINET http://altoproaudio.com</p>	\$420,00
		<p>15" 2 WAY PASSIVE Speaker Power System: 300W continius/ 600W Program/1200W Peak Max SPL at 1m: 122 dB Program / 124.5 dB Peak Frequency Response: (-10dB) 55Hz-20kHz Impedance: 8 Ohms Nominal Crossover Frequency: 2kHz /12 dB/Oct 15mm PAINTED BIRCH PLY CABINET http://altoproaudio.com</p>	\$514,00
PASSIVE SPEAKER SYSTEM		<p>15" 3 WAY PASSIVE Speaker Power System: 350W continius/ 700W Program/1400W Peak Maximum SPL @ 1m: 123 dB nominal / 126 dB peak Impedance: 8 Ω / 4 Ω Coverage (H×V): 90° H × 60° V dual wave guide Connectors: 2 × SPK4 @ Power input / Link Crossover Frequency: 700 Hz - 3 kHz / 12 dB / Octave 15mm PAINTED BIRCH PLY CABINET http://altoproaudio.com</p>	\$895,00
		<p>15" PASSIVE Subwoofer Power System: 400W continius/ 800W Program/1600W Peak Max SPL at 1m: 123 dB Continuous / 126 dB Peak Frequency Response (-10dB): 45 Hz - 200 Hz Impedance: 4 Ohms nominal Crossover Frequency: 160 Hz / 6 dB / Octave 18mm PAINTED BIRCH PLY CABINET http://altoproaudio.com</p>	\$710,00
		<p>18" PASSIVE Subwoofer Power System: 400W continius/ 800W Program/1600W Peak Max SPL at 1m: 123 dB Continuous / 126 dB Peak Frequency Response (-10dB): 35 Hz - 200 Hz Impedance: 4 Ohms nominal Crossover Frequency: 160 Hz / 6 dB / Octave 18mm PAINTED BIRCH PLY CABINET http://altoproaudio.com</p>	\$980,00
BLACK SERIES		<p>10" 2-WAY 2400 WATT LOUDSPEAKER WITH WIRELESS CONNECTIVITY 2400 Watts peak Class D power (1200 Watts continuous) Wireless connectivity for streaming audio,remote setup and sound-shaping control Works with Alto Professional's wireless speaker app for iPad and iPhone 10" low-frequency transducer, 1.75" driver Designed and tuned in the U.S.A. http://altoproaudio.com</p>	\$1.930,00
		<p>15" 2-WAY 2400 WATT LOUDSPEAKER WITH WIRELESS CONNECTIVITY 2400 Watts peak Class D power (1200 Watts continuous) Wireless connectivity for streaming audio,remote setup and sound-shaping control Works with Alto Professional's wireless speaker app for iPad and iPhone 15" low-frequency transducer, 1.75" driver Designed and tuned in the U.S.A. http://altoproaudio.com</p>	\$2.398,00
		<p>2400 WATT 15" ACTIVE SUBWOOFER 2400 Watts peak Class D power (1200 Watts continuous) Powerful 15" low-frequency, long-excursion driver Stereo XLR outputs: left link, right mono, internal crossover on through Switch to turn off logo LED Designed and tuned in the U.S.A. http://altoproaudio.com</p>	\$2.637,00
KICK SERIES		<p>400 WATT INSTRUMENT AMPLIFIER / PA Four-channel amplifier with 400 Watts of peak power 12" low frequency transducer, 1" compression driver Level, effects and high & low EQ controls on all four channels 256 effect presets: 16 effects with 16 variations each http://altoproaudio.com</p>	\$780,00
		<p>400 WATT INSTRUMENT AMPLIFIER / PA Four-channel amplifier with 400 Watts of peak power 15" low frequency transducer, 1" compression driver Level, effects and high & low EQ controls on all four channels 256 effect presets: 16 effects with 16 variations each http://altoproaudio.com</p>	\$910,00
		<p>2 CHANNEL 1000W POWER AMPLIFIER 1000 Watts @ 8 ohm Bridged Mono Class D,Power Amplifier 2x500W@4ohm 2x250W@8ohm With Low Pass Filter http://altoproaudio.com</p>	\$722,00









BLACK SERIES	<p>APX1500</p> 	<p>2 CHANNEL 1500W POWER AMPLIFIER 1500 Watts @ 8 ohm Bridged Mono Class D,Power Amplifier 2x550W@4ohm 2x350W@8ohm With Low Pass Filter</p> <p>http://altoproaudio.com</p>	<p>\$860,00</p>
	<p>APX2000</p> 	<p>4 CHANNEL 2000W POWER AMPLIFIER 2X1000 Watts @ 8 ohm Bridged Mono Class D,Power Amplifier 4x400W@4ohm 4x250W@8ohm With Low Pass Filter</p> <p>http://altoproaudio.com</p>	<p>\$1.380,00</p>
	<p>APX3000</p> 	<p>4 CHANNEL 3000W POWER AMPLIFIER 2X1500 Watts @8 ohm Bridged Mono Class D,Power Amplifier 4x550W@4 ohm 4x350W@8 ohm With Low Pass Filter</p> <p>http://altoproaudio.com</p>	<p>\$1.590,00</p>
MAC POWER AMPLIFIER	<p>MAC 2.3</p> 	<p>2-CHANNEL 2200 WATT POWER AMPLIFIER 2200 Watts @ 4 Ω bridged mono 2 x 1000 Watts @ 2 Ω; 2 x 340 Watts @ 8 Ω Convenient front-panel level controls High-visibility LEDs indicate clipping and protection Switchable 30 Hz low-cut filter Balanced 1/4" and XLR inputs Speakon and binding post outputs Low-noise variable speed fan Compact two rack-space design</p>	<p>\$840,00</p>
	<p>MAC 2.4</p> 	<p>2-CHANNEL 3100 WATT POWER AMPLIFIER 3100 Watts @ 4 Ω bridged mono 2 x 1800 Watts @ 2 Ω; 2 x 670 Watts @ 8 Ω Convenient front-panel level controls High-visibility LEDs indicate clipping and protection Switchable 30 Hz low-cut filter Balanced 1/4" and XLR inputs Speakon and binding post outputs Low-noise variable speed fan Compact two rack-space design</p>	<p>\$980,00</p>
PROCESSORS	<p>ACOM2</p> 	<p>2-CHANNEL COMPRESSOR / LIMITER / GATE Two independent, full-featured compressor/limiters in one compact rack Use as two individual mono processors, or stereo-link to provide true stereo compression Bypass switches on both channels</p> <p>http://altoproaudio.com</p>	<p>\$300,00</p>

FİYATLARIMIZA KDV DAHİL DEĞİLDİR.











SERİ	MODEL	GÖRSEL	AÇIKLAMA	FİYAT
TELSİZ SİSTEMLER	IN64 TEK EL		IN64R RECEIVER 64 UHF channels arranged in 4 preset groups. 300 Ft. (100 meter) operation distance. LCD Displays: RF Level, Audio Level, Low Battery Indicator, Antenna Status, Channel Selection. IN64TH Transmitter 64 selectable channels. Phase-locked Loop (PLL) synthesized tuner. Powered by 2 x AA batteries with 12 hrs. average battery life. LCD display with channel and battery life indicator, ID number. Extended dynamic range and smooth frequency response. Interchangeable capsule module for either condenser or dynamic capsule.	\$580,00
	IN264 ÇİFT EL		IN264R RECEIVER 200~480 meter operation distance. LCD Displays: RF Level, Audio Level, Low Battery Indicator, Antenna Status, Channel Selection. IN264R with band width of 36 MHz. Preset 6 groups, maximum 23 channels in one group. IN264TH Phase-locked Loop (PLL) synthesized tuner. Powered by 2 x AA batteries with 12 hrs. average battery life. LCD display with channel and battery life indicator, ID number. Extended dynamic range and smooth frequency response. Interchangeable capsule module for either condenser or dynamic capsule.	\$1.496,00
	IN264 EL+YAKA		IN264 RECEIVER 200~480 meter operation distance. LCD Displays: RF Level, Audio Level, Low Battery Indicator, Antenna Status, Preset 6 groups, maximum 23 channels in one group. IN264TH Phase-locked Loop (PLL) synthesized tuner. Powered by 2 x AA batteries with 12 hrs. average battery life. IN264TB Phase-locked Loop (PLL) synthesized tuner. Powered by 2 x AA batteries with 12 hrs. average battery life. Equipped with 4 Pin Mini XLR connector.	\$1.516,00
	IN264 ÇİFT YAKA		IN264R RECEIVER 200~480 meter operation distance. LCD Displays: RF Level, Audio Level, Low Battery Indicator, Antenna Status, Channel Selection. IN264R With band width of 36 MHz. Preset 6 groups, maximum 23 channels in one group. IN264TB Phase-locked Loop (PLL) synthesized tuner. Powered by 2 x AA batteries with 12 hrs. average battery life. Equipped with 4 Pin Mini XLR connector. LCD display with channel and battery life indicator, ID number.	\$1.524,00
	US-936K ÇİFTEL		US-936K UHF PLL Dual Channel Diversity Receiver / Transmitter Preset 225 pairs of channels, Innovative channel code 001~225 One key sets two channel, Easy squelch adjustment from front panel Frequency and channel are both adjustable 936K 36MHz super-wide band Phase-locked Loop (PLL) synthesized tuner. Adjustable transmission power between 3mw(Low) & 10mw(Hi) GAIN control -9,-6,-3,0,+3,+6,+9,+12db Frequency and channel are both adjustable	MH- \$648,00

<p>US-8001DB EL</p>		<p>US-8001DB Preset 16 selectable UHF channels.Single / Dual transmitter operation. Tuned antennas maximize the effective range of the wireless link. BNC antenn</p> <p>Mh-750 16 Selectable channels.PLL synthesized control. Advanced circuitry ensures stable signal transmission. Noise mute and Tone-key squelch. Extended dynamic range and smooth frequency response.</p>	<p>\$424,00</p>
<p>US-8001DB YAKA</p>		<p>US-8001DB Preset 16 selectable UHF channels.Single / Dual transmitter operation. Tuned antennas maximize the effective range of the wireless link. BNC antenn</p> <p>PT-850B 16 Selectable channels. Powered by 2 AA batteries. Equipped with 4P Mini XLR connector. Compact, heavy duty plastic housing.</p>	<p>\$456,00</p>
<p>US-8002DB ÇİFTTEL</p>		<p>US-8002DB Preset 16 selectable UHF channels. Single / Dual transmitter operation. Compact half rack space design. BNC antenn</p> <p>Mh-750 16 Selectable channels. PLL synthesized control. Advanced circuitry ensures stable signal transmission. Noise mute and Tone-key squelch. Extended dynamic range and smooth frequency response.</p>	<p>\$768,00</p>
<p>US-8002DB EL+YAKA</p>		<p>US-8002DB Preset 16 selectable UHF channels. Single / Dual transmitter operation. BNC antenn</p> <p>Mh-750 16 Selectable channels. PLL synthesized control.</p> <p>PT-850B 16 Selectable channels. Powered by 2 AA batteries. Equipped with 4P Mini XLR connector.</p>	<p>\$796,00</p>
<p>US-8002DB ÇİFT YAKA</p>		<p>US-8001DB Preset 16 selectable UHF channels. Single / Dual transmitter operation. Tuned antennas maximize the effective range of the wireless link. BNC antenn</p> <p>PT-850B 16 Selectable channels. Powered by 2 AA batteries. Equipped with 4P Mini XLR connector. Compact, heavy duty plastic housing.</p>	<p>\$814,00</p>
<p>US-8001D EL</p>		<p>US-8001D Preset 16 selectable UHF channels. Single / Dual transmitter operation. Diversity technology prevents dropouts in the RF link. Equipped with both XLR balanced and Ø6.3mm unbalanced outputs. Tuned antennas maximize the effective range of the wireless link. BNC anten</p> <p>Mh-750 16 Selectable channels. PLL synthesized control.</p>	<p>\$372,00</p>



<p>US-8001D YAKA</p>		<p>US-8001D Preset 16 selectable UHF channels. Single / Dual transmitter operation. Diversity technology prevents dropouts in the RF link. Equipped with both XLR balanced and Ø6.3mm unbalanced outputs. Tuned antennas maximize the effective range of the wireless link. BNC anten</p> <p>PT-850B 16 Selectable channels. Powered by 2 AA batteries. Equipped with 4P Mini XLR connector.</p>	<p>\$396,00</p>
<p>US-8002D ÇİFT EL</p>		<p>US-8002D Preset 16 selectable UHF channels. Single / Dual transmitter operation. Diversity technology prevents dropouts in the RF link. Tuned antennas maximize the effective range of the wireless link. BNC anten</p> <p>Mh-750 16 Selectable channels. PLL synthesized control. Advanced circuitry ensures stable signal transmission. Noise mute and Tone-key squelch. Extended dynamic range and smooth frequency response.</p>	<p>\$752,00</p>
<p>US-8002D ÇİFT YAKA</p>		<p>US-8002D Preset 16 selectable UHF channels. Single / Dual transmitter operation. Diversity technology prevents dropouts in the RF link. Tuned antennas maximize the effective range of the wireless link. BNC anten</p> <p>PT-850B 16 Selectable channels. Powered by 2 AA batteries. Equipped with 4P Mini XLR connector.</p>	<p>\$768,00</p>
<p>US-8002D EL+YAKA</p>		<p>US-8002D Preset 16 selectable UHF channels. Single / Dual transmitter operation. Diversity technology prevents dropouts in the RF link. Tuned antennas maximize the effective range of the wireless link. BNC anten</p> <p>Mh-750 16 Selectable channels. PLL synthesized control.</p> <p>PT-850B 16 Selectable channels. Powered by 2 AA batteries.</p>	<p>\$760,00</p>
<p>UA-900</p>		<p>ANTENNA DISTRIBUTOR Frequency Range:470 - 870 MHz Provides 4 power supply of DC12V</p>	<p>\$780,00</p>
<p>ANT-952</p>		<p>1/2 wave antenna with BNC connector</p>	<p>\$19,00</p>
<p>USP-900</p>		<p>PASSIVE ANTENNA SPLITTER Full frequency band:470 - 870 MHz Impedance:50Ω</p>	<p>\$52,00</p>

	UDA-49A		ACTIVE UHF DIRECTIONAL ANTENNA Frequency Band:470 - 870 MHz Effective Working Angle:100 degree Antenna Gain:10dB	\$236,00
	UDA-49P		PASSIVE UHF DIRECTIONAL ANTENNA Frequency Band:470 - 870 MHz Effective Working Angle:100 degree Antenna Gain:10dB	\$224,00
HEAD SAET	CM-204U		HEADSET MICROPHONE Connector 4P Mini XLR Frequency Response 30~18,000 Hz Polar Pattern Cardioid Sensitivity (at 1KHz) -68±3 dB* (0.4mV)*0dB=1V/μbar Impedance 680Ω,Max. SPL for 1% THD 130dB Dimension(mm) 205mm(W)* 134mm(H)* 157mm(D) Net Weight 38.4 grams Color: Black	\$128,00
	CM-214F/B		HEADSET MICROPHONE Connector 4P Mini XLR Frequency Response 60~15,000 Hz Polar Pattern Omni-directional Sensitivity (at 1KHz) -60±3 dB* (1mV)*0dB=1V/μbar Impedance 1.8kΩ,Max. SPL for 1% THD 130dB Dimension(mm) 125mm(W)* 134mm(H)* 157mm(D) Net Weight 32.9 grams COLOR: LIGHT BROWN	\$149,00
INSTRUMENT SYSTEM	CX-505		CONDENSER DRUM & PERCUSSION MICROPHONE Type Electret Condenser - Frequency Response 50~18,000 Hz Polar Pattern Cardioid Sensitivity(at 1,000Hz) -64dB*(0.63mV) at 1,000 Hz Output Impedance 220Ω ± 30% - Max. SPL for 1% THD 130 dB Output connector 3P. XLR (M) type Net Weight Metallic enamel-painted die cast metal body with hardened, matte-finished steel grille Net Weight 230 grams (8.1 oz) Touch Noise. Super low - Power Supply 9-52V phantom power	\$135,00
MIKROFONLAR	NX-7		DYNAMIC MICROPHONE CAPSULE Type Moving Coil Dynamic Frequency Response 50~16,500 Hz Polar Pattern Cardioid,rotationally symmetrical about microphone axis, uniform with frequency Sensitivity(at 1,000Hz) -72dB*(0.25mV)*0dB=1V/μbar Impedance 600Ω Phasing Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3 Connector Three-pin professional audio connector (male XLR type)	\$119,00
	NX-8		VOCAL PERFORMANCE MICROPHONE Type Moving Coil Dynamic Frequency Response 50~16,500 Hz Polar Pattern Cardioid,rotationally symmetrical about microphone axis, uniform with frequency Sensitivity(at 1,000Hz) -72dB*(0.25mV)*0dB=1V/μbar Impedance 600Ω Phasing Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3 Connector Three-pin professional audio connector (male XLR type)	\$120,00
	NX-8.8		VOCAL CONDENSER MICROPHONE Type Electret Condenser Frequency Response 60~18,000 Hz Polar Pattern Supercardioid,rotationally symmetrical about microphone axis, uniform with frequency Sensitivity(at 1,000Hz) -70dB*(0.32mV)*0dB=1V/μbar Output Impedance 400Ω Phasing Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3 Connector Three-pin professional audio connector (male XLR type)	\$190,00






<p>CX-07S</p>		<p>MULTIPURPOSE MICROPHONE Type Moving Coil Dynamic Frequency Response 50~16,500 Hz Polar Pattern Cardioid Sensitivity (at 1,000Hz) -72dB*(0.25mV)*0dB=1V/μbar Impedance 600Ω Net Weight 245 grams (8.6 oz)</p>	<p>\$90,00</p>
<p>TM-929</p>		<p>PERFORMANCE MICROPHONE Type Moving Coil Dynamic Frequency Response 50~15,000 Hz Polar Pattern Cardioid,rotationally symmetrical about microphone axis, uniform with frequency Sensitivity (at 1,000Hz) -75dB*(0.18mV)*0dB=1V/μbar Impedance 600Ω</p>	<p>\$60,00</p>
<p>TM-989</p>		<p>PERFORMANCE MICROPHONE Type Moving Coil Dynamic Frequency Response 80~12,000 Hz Polar Pattern Cardioid,rotationally symmetrical about microphone axis, uniform with frequency Sensitivity (at 1,000Hz) -75dB*(0.18mV)*0dB=1V/μbar Impedance 600Ω</p>	<p>\$50,00</p>
<p>TX-9</p>		<p>INSTRUMENT CONDENSER MICROPHONE Type Electret Condenser Frequency Response 60~18,000 Hz Polar Pattern Cardioid,rotationally symmetrical about microphone axis, uniform with frequency Sensitivity(at 1,000Hz) -70dB* (0.32mV)*0dB=1V/μbar Output Impedance 400Ω Phantom Power Requirements 9-52 VDC</p>	<p>\$120,00</p>
<p>TK-280</p>		<p>PERFORMANCE MICROPHONE Type Moving Coil Dynamic Frequency Response 50~15,000 Hz (TK-600) 80~12,000 Hz (TK-350/TK-280) Polar Pattern Cardioid,rotationally symmetrical about microphone axis, uniform with frequency Sensitivity (at 1,000Hz) -75dB*(0.18mV)*0dB=1V/μbar Impedance 600Ω</p>	<p>\$110,00</p>
<p>SX-7S</p>		<p>MULTIPURPOSE MICROPHONE Type Moving Coil Dynamic Frequency Response 50~16,500 Hz Polar Pattern Cardioid,rotationally symmetrical about microphone axis, uniform with frequency Sensitivity(at 1,000Hz) -77dB*(0.14mV)*0dB=1V/μbar Impedance 250Ω Phasing Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3 Connector Three-pin professional audio connector (male XLR type)</p>	<p>\$134,00</p>
<p>GM-5212L</p>		<p>GOOSENECK MICROPHONE 12" (305mm) Gooseneck Length Electret Condenser 125 dB Impedance -60dB (1mV) Frequency Response: 80 ~ 18,000 Hz Polar pattern: Supercardioid</p>	<p>\$120,00</p>




GM-5218L		GOOSENECK MICROPHONE 18" (457mm) Gooseneck Length Electret Condenser 125 dB Impedance -60dB (1mV) Frequency Response: 80 ~ 18,000 Hz Polar pattern: Supercardioid	\$130,00
GM-5225L		GOOSENECK MICROPHONE 25" (585mm) Gooseneck Length Electret Condenser 125 dB Impedance -60dB (1mV) Frequency Response: 80 ~ 18,000 Hz Polar pattern: Supercardioid	\$150,00
GM-5215LDU		GOOSENECK MICROPHONE 15"(335 mm) Impedance 220 Ω Frequency Response 80 · 18,000 hz Hz Polar Pattern: Supercardioid	\$270,00
ST-850		WIRELESS/WIRED GOOSENECK MICROPHONE Back Electret Condenser Frequency Response: 50 - 18,000 Hz Polar pattern: Supercardioid Impedance Wireless: 2kΩ Wired: 12-48 VDC phantom power Power Supply Wireless: 5VDC Wired: 12-48VDC phantom power	\$212,00
ST-5030		UNIVERSAL WIRED GOOSENECK Microphone Base Frequency response: 20~20,000 Hz Power requirement: Phantom power 12V/microphone stand base 2x1,5V battery/phantom power 9V - 50V	\$130,00
ST-5070		SHOCKMOUNT PLATE Shockmount plate with XLR (F) con	\$80,00
CM-501		Condenser Lavalier Microphone Connector 4P Mini XLR, Frequency Response 100~15,000 Hz Polar Pattern Cardioid, Sensitivity (at 1KHz) -60±3 dB* (1mV)*0dB=1V/μbar Impedance 2.2kΩ, Max. SPL for 1% THD 130dB Dimension(mm) Ø10.1mm(W)* 26.4mm(H), Net Weight 21.5g	\$66,00
MH-750		UHF PLL Handheld Transmitter Carrier Frequency Range 502~960 MHz, RF Outputs 10mW, Stability ±10KHz Frequency Deviation ±48KHz, Controls Power On/Off, Channel Selecting Spurious Emissions <-50 Dbc, Audio Frequency Response 50~16,000 Hz	\$196,00
MH-850		UHF PLL Handheld Transmitter Carrier Frequency Range 502~960 MHz, RF Outputs 10mW Stability ±10KHz, Frequency Deviation ±48KHz Controls Power On/Off, Channel Selecting, Spurious Emissions <-50 dBC Audio Frequency Response 50~16,000 Hz	\$216,00
PT-850B		UHF PLL Body-Pack Transmitter Carrier Frequency Range 502~960 MHz, RF Outputs 10mW Frequency Deviation ±48KHz, Controls Power On/Off, AF Level, Channel Selecting Audio Frequency Response 40~18,000 Hz, Battery UM3, AA 1.5V*2	\$190,00
DMC-700		Detachable Capsule Module Type Dynamic, Frequency Response 50~16,000 Hz Polar Pattern Hypercardioid, Output Level(1,000Hz) -80±3dB Impedance DMC-1: 600Ω , DMC-3: 750Ω	\$68,00

DMC-800		Detachable Capsule Module Type Dynamic, Frequency Response 50~16,000 Hz Polar Pattern Hypercardioid, Output Level(1,000Hz) -80±3dB Impedance DMC-1: 600Ω , DMC-3: 750Ω	\$86,00
FGM-62 CARBON		Type Back Electret Condenser Frequency Response 50~18,000 Hz Polar Pattern Cardioid, Supercardioid, Omni-directional Sensitivity (at 1,000Hz) -56±3dB(1.58mV) 0dB=1V/μbar Impedance 220Ω, Max. SPL for 1% T.H.D. 125 dB Connector 3P mini XLR (M), Cable Connector Input: 3P mini-XLR (F) Output: 3P XLR (Power Module), Power Supply 9-52 VDC phantom power (LED standard Operation voltage 48V) Cable Length 8m , Stand height : 62cm	\$310,00
FGM-170 CARBON		Type Back Electret Condenser Frequency Response 50~18,000 Hz Polar Pattern Cardioid, Supercardioid, Omni-directional Sensitivity (at 1,000Hz) -56±3dB(1.58mV) 0dB=1V/μbar Impedance 220Ω, Max. SPL for 1% T.H.D. 125 dB Connector 3P mini XLR (M), Cable Connector Input: 3P mini-XLR (F) Output: 3P XLR (Power Module), Power Supply 9-52 VDC phantom power (LED standard Operation voltage 48V), Cable Length 8m, Stand height : 170cm	\$348,00
CM-602		Boundary Microphone Frequency Response 30~12,000 Hz Sensitivity (at 1,000Hz) -53±3 dB* (2.23mV) 0dB=1V /μbar Directional Pattern Half-Cardioid, Impedance 100Ω Max. SPL for 1% THD 125 dB - Signal-To-Noise Ratio 67dB Power Supply 12-52 VDC phantom power - Current Consumption ≤6mA Output Connector 3P Mini XLR-M type(power module) Net Weight 88 grams - CM-601 Only 0, Low Frequency Roll-off 80Hz , 120Hz, Switches Push control: on/off - Function selection: push on/off, momentary on/off, Low cut : low frequency roll-off	\$116,00
CM-502		Choir Microphone Type Electret Condenser Frequency Response 100~18,000 Hz, Polar Pattern Supercardioid Sensitivity (at 1,000Hz) -48dB*(4mV)*0dB=1V/μbar Impedance 220Ω, Max. SPL for 1% THD 125dB Connector male XLR type, Standard Accessories Windscreen / Flexible hanger / Mounting plate	\$140,00
CM-503U		Low Profile Boundary Microphone Type Electret Condenser, Frequency Response 40 to 20,000Hz Polar Pattern Half-Cardioid, Sensitivity (at 1,000Hz) -60±3dB* (1mV)* 0dB=1V/μbar Attenuation Switch -10dB, Low Frequency Roll-off 80Hz Impedance 220Ω, Max. SPL For 1% T.H.D. 140 dB Signal To Noise Ratio 70dB, Current Consumption ≤3mA Power Supply 9-52 VDC phantom power Output Connector XLR-M type(power module)	\$86,00
CS-1CU		CS-1CU Digital Central Unit The chairman unit not only provides the same function as the delegate unit, but also supports the addition of a "Priority button", that enables the chairman to control the discussion by temporary or permanently overriding and deactivating all active microphones of the delegate units.	\$680,00
CS-1CH		CS-1CH Chairman Unit The chairman unit not only provides the same function as the delegate unit, but also supports the addition of a "Priority button", that enables the chairman to control the discussion by temporary or permanently overriding and deactivating all active microphones of the delegate units	\$350,00
CS-1DU		CS-1DU Delegate Unit The delegate unit enables the attendants to participate in a discussion by speaking through a microphone, controlled by a microphone ON/OFF push-button, and listening to discussion by the internal loudspeaker and external headphone.	\$330,00














CS-1EXM	 A black rectangular expansion kit with two 7-pin DIN connectors. The left connector is labeled 'CS-1EXM' and the right one is labeled 'CS-1EXM'. A red 'YENI' (New) badge is in the top right corner.	CS-1EXM Expansion Kit Input 7-pin DIN Connector Output 7-pin DIN Connector Dimension(mm) 115mm(W)* 65mm(D)* 38mm(H)	\$80,00
CS-1EXS	 A black rectangular expansion kit with two 7-pin DIN connectors. The left connector is labeled 'CS-1EXS' and the right one is labeled 'CS-1EXS'. A red 'YENI' (New) badge is in the top right corner.	CS-1EXS Expansion Kit Input 7-pin DIN Connector Output 7-pin DIN Connector Dimension(mm) 115mm(W)* 65mm(D)* 38mm(H)	\$92,00

















FİYATLARIMIZA KDV DAHİL DEĞİLDİR.

SERİ	MODEL	GÖRSEL	AÇIKLAMA	FİYAT
TELSİZ MİKROFONLAR	R 1001 & Q1002		R-1001 Frequency Range VHF Switchable Frequencies 1 - Channels 1 Oscillation Type Crystal fixed - Frequency Stability $\pm 0.005\%$ Receiving Method Non Diversity - Sensitivity -90dBm Image Rejection > 60dB -S/N Ratio > 105dB Antenna Socket Fixed type - Audio Outputs 6.3mm *1 Q-1002 Handheld Transmitter Frequency Range VHF 160-260 MHz Switching Bandwidth - Switchable Frequency 1 RF Power Output < 35mW** Spurious Emission > 40dB below carrier Dynamic Range > 100 dB - T.H.D < 0.5% Operating Life (Alkaline) 16 hours	\$200,00
	R 1001 & M1002		R-1001 Frequency Range VHF Switchable Frequencies 1 - Channels 1 Oscillation Type Crystal fixed - Frequency Stability $\pm 0.005\%$ Receiving Method Non Diversity - Sensitivity -90dBm Image Rejection > 60dB -S/N Ratio > 105dB Antenna Socket Fixed type - Audio Outputs 6.3mm *1 M-1002 Frequency Range VHF 160-260 MHz Switching Bandwidth - Switchable Frequency 1 RF Power Output < 35mW** Dynamic Range > 100 dB Operating Life (Alkaline) 16 hours - Connector 4-pin mini XLR type	\$230,00
	R 2001 & 2 x Q 1002		R-2001 Frequency Range VHF Switchable Frequencies 1 - Channels 2 Oscillation Type Crystal fixed - Frequency Stability $\pm 0.005\%$ Receiving Method Non Diversity - Sensitivity -90dBm Image Rejection > 60dB -S/N Ratio > 105dB Peak Deviation $\pm 15\text{KHz}$ -T.H.D. < 0.5% Q-1002 handheld transmitter Frequency Range VHF 160-260 MHz Switching Bandwidth - Switchable Frequency 1 RF Power Output < 35mW** Spurious Emission > 40dB below carrier Dynamic Range > 100 dB - T.H.D < 0.5% Operating Life (Alkaline) 16 hours	\$320,00
	R 2001 & 2 x M 1002		R-2001 Frequency Range VHF Switchable Frequencies 1 - Channels 2 Oscillation Type Crystal fixed - Frequency Stability $\pm 0.005\%$ Receiving Method Non Diversity - Sensitivity -90dBm Image Rejection > 60dB -S/N Ratio > 105dB Peak Deviation $\pm 15\text{KHz}$ -T.H.D. < 0.5% Antenna Socket Fixed type - Audio Outputs 6.3mm *1 M-1002 Frequency Range VHF 160-260 MHz Switching Bandwidth - Switchable Frequency 1 RF Power Output < 35mW** - Dynamic Range > 100 dB Operating Life (Alkaline) 16 hours - Connector 4-pin mini XLR type	\$360,00
	R 2001 & Q 1002 & M 1002		R-2001 Frequency Range VHF / Switchable Frequencies 1 - Channels 2 Oscillation Type Crystal fixed - Frequency Stability $\pm 0.005\%$ Receiving Method Non Diversity - Sensitivity -90dBm Image Rejection > 60dB -S/N Ratio > 105dB Peak Deviation $\pm 15\text{KHz}$ -T.H.D. < 0.5% Antenna Socket Fixed type - Audio Outputs 6.3mm *1 Q-1002 handheld transmitter Frequency Range VHF 160-260 MHz / Switching Bandwidth - Switchable Frequency 1 RF Power Output < 35mW** - Spurious Emission > 40dB below carrier Dynamic Range > 100 dB - T.H.D < 0.5% -Operating Life (Alkaline) 16 hours M-1002 Frequency Range VHF 160-260 MHz - Switching Bandwidth - Switchable	\$340,00

HEADSET	MC 72		MC-72 Microphone type Condenser Sensitivity -50dB (0dB=1v/pa at 1KHz) Output Impedance 680Ω at 1KHz Directionality Uni-directional Frequency Response 100~16000Hz Operation Voltage 1.5V~10V Connector XLR Weight (g) 45	\$65,00
	MC 76B		MC-76B Microphone type Condenser Sensitivity -46dB (0dB=1V/Pa at 1KHz) Output Impedance 2.2KΩ at 1KHz Directionality Omni-directional Frequency Response 100~18000Hz Operation Voltage 1.0~10V Connector XLR - Weight (g) 26	\$78,00
AKSESUARLAR	MC 16		MC-16 Microphone type Condenser Sensitivity -60dB (0dB=1V/Pa at 1KHz) Output Impedance 1KΩ at 1KHz Directionality Uni-directional Frequency Response 80~16000Hz Operation Voltage 1.5~10V Current Consumption \leq 0.5mA Signal to Noise Ratio \geq 60dB Connector XLR - Weight (g) 20	\$52,00










FİYATLARIMIZA KDV DAHİL DEĞİLDİR.

SERİ	MODEL	GÖRSEL	AÇIKLAMA	FIYAT
CHALLENGER SERİSİ HOPARLÖRLER			C18-650EL RECONE KIT	\$290,00
			C18-600LF RECONE KIT	\$290,00
	C15-600EL		15" LOW FREQUENCY TRANSDUCER 600 Watt Power Rating 8 Ohm Nominal Impedance 98 dB Sensitivity 30Hz-1.2K Hz. Freq. Range	\$630,00
			C15-600EL RECONE KIT	\$236,00
	C15-500LF		NOMINAL BASKET DIAMETER 15" Impedance 8 ohms RMS Power Rating 500 Watts Program Power 1000 Watts Frequency Response 30Hz - 1.2kHz Sensitivity (1W/1m) 97dB Voice Coil Diameter 4" / 101.6mm	\$590,00
			C15-500LF RECONE KIT	\$210,00
	C15-400B		15" LOW Frequency Transducer 400 Watt Power Rating 8 Ohm Nominal Impedance 97.9 dB Sensitivity 30Hz-2.0K Hz. Freq. Range	\$520,00
			C15-400B RECONE KIT	\$188,00
	C15-300MB		NOMINAL BASKET DIAMETER 15" Impedance 8 ohms, Rms power rating 300 Watt Program power 600 Watt Frequency response 35Hz-3.2 KHz	\$470,00
			C15-300MB RECONE KIT	\$180,00
C12-500MB		12" MID & BASS TRANSDUCER 500 Watt Power Rating 8 Ohm Nominal Impedance 95 dB Sensitivity, 60-3000 Hz. Freq. Range	\$432,00	
C12-300MB		12" MID & BASS TRANSDUCER 500 Watt Power Rating 8 Ohm Nominal Impedance 95 dB Sensitivity, 60-3000 Hz. Freq. Range	\$410,00	
		C12-300MB RECONE KIT	\$146,00	
P150/2226		380mm/15" High Power Low Frequency Woofer Power: 600W	\$520,00	
SN SERİSİ HOPARLÖRLER	SN-15B		15" HIGH OUTPUT NEODYMIUM BASS SUBWOOFER Power Rating: 300W RMS Frequency Response: 35-2.5kHz Sensitivity: 100db, Impedance: 8 ohms Voice Coil: 3" glass fiber Resonant Frequency: 39 Hz	\$490,00
	SN-8MB		Nominal Impedance 8 Ω Power 150 Watt (rms) SPL 1W@1M average sensitivity 95 dB Frequency Response 60Hz - 2000Hz Dimension Ø x H (cm) 21.4 x 10.0 Net Weight 2 kg (4.4 lbs)	\$230,00
			E15-350N-RECONE KIT	\$146,00
E SERİSİ HOPARLÖRLER			E15-300S-RECONE KIT	\$94,00
	E15-200S		15" LOW & BASS TRANSDUCER Power Rating: 200-400W Resonant Frequency: 41 Hz Nominal Impedance: 4-8 Ohm	\$210,00
	E15W		15" HIGH POWER WHIZZER CONEFULL Range Power: 400/800W	\$370,00
	E12W		12" HIGH POWER WHIZZER CONEFULL RANGE Power Rating: 400/800W	\$200,00
			E12W RECONE KIT	\$72,00
	E12-350N		3" VOICE COIL 1400 Watts Peak Power Handling Power Rating: 350W Resonant Frequency: 64 Hz Nominal Impedance: 8 Ohm	\$410,00
		E12-300S-RECONE KIT	\$82,00	




IMF SERİSİ HOPARLÖRLER	E12-300SE		12" MID & BASS TRANSDUCER Power Rating: 300W Resonant Frequency: 47 Hz Nominal Impedance: 4-8 Ohm	\$200,00	
				E12-200S-RECONE KIT	\$55,00
				IMF-HP18W-RECONE KIT	\$128,00
	IMF-HP15W		1200 WATTS PEAK POWER HANDLING 380mm/15" High Power Bass Power: 200~400W Empedans: 7.2 Ohm Hassasiyet (1w/1m): 96dB	\$200,00	
				IMF-HP15W-RECONE KIT	\$74,00
	IMF-HP12W		1200 WATTS PEAK POWER HANDLING 380mm/15" High Power Bass Power: 200~400W Empedans: 7.2 Ohm Hassasiyet (1w/1m): 96dB	\$124,00	
			IMF-HP12W RECONE KIT	\$45,00	
IMF-HP-12T		305mm/12" HIGH POWER BASS & FULL RANGE Power:100~200W Empedans: 7.2 Ohm Hassasiyet (1w/1m): 96dB	\$130,00		
BM SERİSİ COMPRESSION ÜNİTLER	BM-D740/BM-D750 DIAPHRAGM		Bobin boyutu: 72.2mm (72.5mm) Bobin empedansı: 8 ohm (DC testi 5-8 ohm) Sütun merkezi mesafesi: 120mm Dış çapı konumlandırma: 107mm Szie hatası: +/- 2mm	\$150,00	
	BM-D450S II		HIGH OUTPUT COMPRESSION DRIVER Power Handling: 60 Watt Nominal Impedance: 8 Ohm Sensitivity:110dB	\$200,00	
	BM-D440S II		HIGH OUTPUT COMPRESSION DRIVER Power Handling: 50 Watt Nominal Impedance: 8 Ohm Sensitivity:108dB	\$175,00	
				BM-D440/BM-D450 DIAPHRAGM	\$80,00
PA SERİSİ DRIVER ÜNİTLER	PA-D110		WEATHER RESISTANT MID RANGE AND HIGH FREQUENCY COMPRESSION DRIVER Throat Diameter: 0.87" (22mm) Diaphragm Diameter: 2" (50mm) Power Handling: 75 Watt Nominal Impedance: 16 Ohm	\$110,00	
	PA-D25		SMALL FORMAT DIAPHRAGM COMPRESSION DRIVER Throat Diameter: 1" Diaphragm Diameter: 1" (25.4mm) Power Handling: 30 Watt Nominal Impedance: 8 Ohm	\$65,00	
				PA-D25 DIAPHRAM	\$33,00
	PA-D32		SMALL FORMAT DIAPGRAGM COMPRESSION DRIVER Throat Diameter: 1" Diaphragm Diameter: 1" (25.4mm) Power Handling: 30 Watt rms Nominal Impedance: 7.4 Ohm	\$260,00	
	PA-D32 DIAPGHRAM		1" screw-on compression driver	\$140,00	
	PA-D415S		Small Format Diaphragm Compression Driver Throat Diameter: 1" (25.4mm) Diaphragm Diameter:1.35" (34.4mm) Power Handling: 20 Watt Nominal Impedance: 8 Ohm	\$120,00	
			PA-D38 DIAPGHRAM	\$60,00	
HORNLAR	PH-14525		Horn For Professional Driver Throat Diameter: 1"	\$130,00	
	HORN AL PH-CL35		Cut Off Frequency (Hz.) 1000Hz Throat Diameter 35.5 mm (1.4") Mounting Type BOLT ON	\$160,00	
PC-20 SILVER ROHS		Horn ve Driver Adaptor 68 x 24 mm Alüminyum	\$13,00		
	PC-35 ROHS		Horn ve Driver Adaptor 89 x 25 mm Alüminyum	\$18,00	








ADAPTÖRLER	PC-60 BLACK ROHS		Horn ve Driver Adaptor 180 x 115 mm Alüminyum	\$135,00
	PC-70 BLACK ROHS		ADAPTOR	\$123,00
	PC-5025 BLACK ROHS		Horn ve Driver Adaptor 120 x 76 mm Alüminyum	\$88,00
	PC-5038 BLACK ROHS		Horn ve Driver Adaptor 120 x 47 mm Alüminyum	\$130,00
X SERİSİ	X-15P		Two-Way Full Range Passive Bass Reflex Power Handling: 1000 Watt Sensitivity 1W@1M: 98 dB Freq. Response: 50Hz-20kHz Nominal Impedance: 8 Ohm	\$1.050,00
	X-15HP		Two-Way Full Range Passive Bass Reflex Power Handling: 1200 Watt Sensitivity 1W@1M: 98 dB Freq. Response: 50Hz-20kHz Nominal Impedance: 8 Ohm	\$1.550,00


FİYATLARIMIZA KDV DAHİL DEĞİLDİR.




SERİ	MODEL	GÖRSEL	AÇIKLAMA	FİYAT
GİTAR HOPARLÖRLERİ	VINTAGE 30		Nominal diameter : 12", 305mm Power rating : 60W rms Nominal impedance Available 8Ω Sensitivity : 100dB Chassis type Pressed steel Voice coil diameter 1.75", 44.5mm Voice coil material Round copper Magnet type : Ceramic Magnet weight 50oz, 1.42kg Frequency range : 70-5000Hz Resonance frequency, Fs :75Hz	\$310,00
GİTAR HOPARLÖRLERİ	TF 0615MR		6" / 50W / 1.5" / 500Hz-5kHz / 97dB / 500Hz	\$80,00
GİTAR HOPARLÖRLERİ	TF 0818MR		8" / 100W / 1.75" / 800Hz-5kHz / 99dB / 450Hz	\$98,00
TRUVOX SERIES SPEAKER	TF 1218TC		12" / 100W / 1.75" / 50Hz-8kHz / 98dB / 56Hz	\$170,00
	TF 1225		12" / 250W / 2.5" / 50Hz-4kHz / 97dB / 63Hz	\$190,00
	TF 1225e		12" / 300W / 2.5" / 50Hz-3kHz / 96dB / 61Hz	\$230,00
	TF 1525e		15" / 300W / 2.5" / 45Hz-3.5kHz / 98dB / 44Hz	\$270,00
	TF 1530		15" / 400W / 3" / 40Hz-3kHz / 99dB / 42Hz	\$310,00
CDX SERIES TWEETERS	CDX1-1415		1" / 20W / 1.4" / AL / 104dB / 2.5kHz / Bolt	\$140,00
















FİYATLARIMIZA KDV DAHİL DEĞİLDİR.

SERİ	MODEL	GÖRSEL	AÇIKLAMA	FİYAT
ANFİLER	SA-100UT		SA-100UT 70/100V - 8 Ohm 100W Kısa Devre Koruma Usb/MP3 Giriş 2 Mic. Giriş, 2 Aux In 1 Aux Out, 1 Priority Bass, Tiz Kontrol Uzaktan Kumanda, Ldc Ekran, Stand By Kontrol, 10 Mt Bluetooth Mesafesi	\$90,00
	SA-150UTZ		SA-150UTZ 70/100V - 8 Ohm 150W Kısa Devre Koruma 2 Bölge Bağımsız Ses Kontrolü Usb/MP3 Giriş 2 Mic. Giriş, 1 Aux In 1 Aux Out, 1 Priority Bass, Tiz Kontrol Uzaktan Kumanda, Lcd Ekran, Stand By Kontrol, 10 Mt Bluetooth Mesafesi	\$110,00
	SA-200UTZ		SA-200UTZ 70/100V - 8 Ohm 200W Kısa Devre Koruma 3 Bölge Bağımsız Ses Kontrolü Bluetooth-Usb/MP3 2 Mic. 2 Aux In 1 Link In, 1 Rec Out, 1 Priority, Siren ve Dingdong Lcd Ekran - Id Tag Bass, Tiz, Echo, Delay, Repeat Effect Uzaktan Kumanda Stand By Kontrol	\$220,00
	SA-250UTZ		SA-250UTZ 70/100V - 8 Ohm 250W Kısa Devre Koruma 6 Bölge Bağımsız Ses Kontrolü Bluetooth-Usb/MP3 4 Mic. 3 Aux In 1 Link In, 1 Rec Out, 1 Priority, Siren ve Dingdong Lcd Ekran - Id Tag Bass, Tiz, Echo, Delay, Repeat Effect Uzaktan Kumanda Stand By Kontrol	\$330,00
ANFİLER	SCR-150		SCR-150 100W GÜCÜNDE 4 KANAL MİKROFON VE LINE GİRİŞ KISA DEVRE KORUMALI	\$200,00
	SCR-150T		SCR-150T 100W GÜCÜNDE 4 KANAL MİKROFON VE LINE GİRİŞ KISA DEVRE KORUMALI	\$230,00
	SCR-250		SCR-250 250 W GÜCÜNDE 4 KANAL MİKROFON VE LINE GİRİŞ KISA DEVRE KORUMALI	\$230,00
	SCR-250T		SCR-250T 250 W GÜCÜNDE 4 KANAL MİKROFON VE LINE GİRİŞ KISA DEVRE KORUMALI	\$260,00
	SCR-400		SCR-400 400 W GÜCÜNDE 4 KANAL MİKROFON VE LINE GİRİŞ KISA DEVRE KORUMALI	\$260,00
	SCR-400T		SCR-400T 400 W GÜCÜNDE 4 KANAL MİKROFON VE LINE GİRİŞ KISA DEVRE KORUMALI	\$300,00
MİKROFONLAR	DM-58		DİNAMİK MİKROFON 600 OHM, 6,3 mm Jaklı, Polar Pattern Cardioid (Uni Directional), Frequency Response 80Hz ~ 12,000Hz Sensitivity-72dB ± 3dB (SPL=74dB 0dB=1V/ µ Bar; at 1KHz) Dimensions (mm): Ø52 x 178, Ağırlık 275g	\$40,00
	DM-210		DİNAMİK MİKROFON 600 OHM, 6,3 mm Jaklı, Polar Pattern Cardioid (Uni Directional), Frequency Response 80Hz ~ 12,000Hz Sensitivity-72dB ± 3dB (SPL=74dB 0dB=1V/ µ Bar; at 1KHz) Dimensions (mm): Ø52 x 178, Ağırlık 225g	\$30,00




















CTP-10DX		CLIP MICROPHONE CONDENSER Type: Tie-Clip Electret Condenser Frequency Response: 100-15,000Hz Sensitivity: 5m V/Pa Impedance: 1,000 ohm Power Requirement: 1.5V Pencil Cell 1x Clip Conder Microphone 1x Sponge Cover 1x 5m Cable 1x AA Battery	\$30,00
SH-181UR		WAISTBAND PA AMPLIFIER With TF card slot and USB slot RMS:10W max, THD-20% in full battery level Output Power: 15W max, DC 9V input Frequency Responser: 100Hz-20KHz (-3dB) Distortion Factor: 1% (1W) Audio input: Stereo 250mV Operating temperature: -10-45C Dimensions (WXHXD): 127x103x48.5mm Weight: 320g 30PCS IN ONE CARTON	\$90,00
SH-222U USB		PORTATIF ÇANTA ANFI Lightweight, compact and rugged encloure VHF high band wireless tie-clip/beltack mic system Tone Control and independent volume controls 6.5mm dynamic microphone input jack Built-in rechargeable battery and charger Audio (MP3) input jack 8 ohm external speaker output jack Frequency range: VHF174-216MHZ AUX input port USB input port SD card input port U-disk/SD recording MP3 remote controller	\$160,00
SH-220 USB		PORTABLE WIRELESS PA AMPLIFIER Main Framw with DC 2.2AH rechargeable battery Built-in DC 8.4V rechargeable battery charger Three types of power source supply Power source capacity LED 4 ohm speaker external output DC 12V 1A input USB/SD play MP3 LCD display Wired MIC Wireless MIC Wireless amplifying Digital echo Digital tone U-disk/SD recording MP3 remote controller	\$300,00
SH-668U USB		PORTABLE WIRELESS PA AMPLIFIER Main frame with 7AH rechargeable battery DC 8.4V rechargeable battery charging LED DC 12V rechargeable battery charging LED Power source capacity LED 4 ohm External loudspeaker output Wireless amplifying SD card input port USB input port AUX input & output 2 Wired MICS Input 2 Wireless MICS Dual channels Digital tone Echo U-disk/SD recording	\$480,00
SH-730B USB		PORTABLE WIRELESS PA AMPLIFIER Power Supply: AC 220V/50Hz 2A RMS Power: 400W Max Service Range: 35M Max Frequency Range: VHF 174-216MHz Frekans aralıđı VHF 174-216 MHz Frekans karđılıđı: 25,15000 Hz Dimensions: 430X360X600mm Gross weight: 26kgs Bluetooth özelliđli	\$700,00
WS-659 5"		5" 2 WAY WALL SPEAKER Woofer 1x5.25" Tweeter 1x0.76VC Impedance 4 Ohms Power Rating 120W Max. Frequency Response 60Hz-20KHz Sensitivity 91 dB (1M/1W) 100V Line Voltage	\$80,00
WS-659 6.5"		6.5" 2 WAY WALL SPEAKER Woofer 1x6.5" Tweeter 1x1VC Impedance 4 Ohms Power Rating 150W Max. Frequency Response 60Hz-20KHz Sensitivity 90 dB (1M/1W) 100V Line Voltage	\$100,00

WS - 651		6,5" WALL SPEAKER Line Voltage: 100V RMS Power: 10W Transformer: 10W Speaker unit: 6.5" x1 Response Frequency: 150Hz-15KHz Sensitivity(1m/1w):91dB Dimension: 180x80x220mm	\$22,00
WS-728L		6.5" WALL SPEAKER Line Voltage: 100V RMS Power: 10W Transformer: 10W Speaker unit: 6.5" x1 Response Frequency: 150Hz-15KHz Sensitivity(1m/1w):91dB Dimension: 180x80x220mm	\$28,00
L-620		4" WALL MOUNTED SPEAKER Power: 120W Max With transformer, input 100V Frequency: 90Hz-20KHz Sensitivity (1w/m): 90dB Speaker Impedance: 8 ohms	\$80,00
L-630		5" WALL MOUNTED SPEAKER Power: 150W Max With transformer, input 100V Frequency: 75Hz-20KHz Sensitivity (1w/m): 90dB Speaker Impedance: 8 ohms	\$100,00
L-640		6.5" WALL MOUNTED SPEAKER Power: 200W Max With transformer, input 100V Frequency: 75Hz-20KHz Sensitivity (1w/m): 90dB Speaker Impedance: 8 ohms	\$120,00
Y-705		5" CEILING SPEAKER Size: 180xH63mm Input: 100V Duyarlılık: 91dB Frekans Tepkisi: 90Hz-16KHz	\$20,00
A-9774		FASHION SPEAKER Woofers: 4" Middle Range: 2" Power: 100W Max Impedance: 8 ohms With Transformer 100V input Input: 100V Frequency Response: 80HZ-20KHZ Sensitivity: 101dB Size: 240x145x120mm Trafo : 100V - 100V Renk: Siyah/Beyaz	\$50,00
HWR 121T		2x5" WALL SPEAKER Load rating at 100V: 10W Frequency range: 110-16 KHz. Speaker Ø and Impedance : 2 x 5" / 8 ohms. ABS white. Size: 213 x 290 x 130 mm	\$45,00
HVC86-1 10W		VOLUME SELECTOR 5 Level 86x86 mm 10W - WITH TRANSFORMER	\$20,00
DR-004		PIEZO DRIVER Frequency Response:1.5-20 KHz Sensitivity:105dB (2.83V/1m) Impedance: 4Ω / 8 Ω Power: RMS/MAX : 20W/60W	\$8,00
DR-012		DRIVER UNIT Magnet: Φ80x12. Voice coil Φ25.5 Cloth. Frequency Response: 1.5-20 KHz Sensitivity: 107dB (2.83V/1m) Impedance: 4Ω / 8 Ω Power: RMS/MAX: 40W/120W	\$20,00
VC-25.5 TI (YH-300T)		DIAPHRAGM DØ25.5mm 8 Ohms	\$5,00















DRIVER UNIT	GD-023		DRIVER UNIT Voice Coil: Ø34.4mm Titanium Frequency Response: 1-20KHz Sensitivity: 106dB Impedance: 8Ω Power: RMS/MAX: 40W/120W	\$35,00
	VC-34TI		DIAPHRAGM Ø34.4mm 8 Ohms	\$14,00
	GD-017		DRIVER UNIT Voice Coil Ø44.4mm Freq. Resp: 1.2-20KHz Sensitivity: 106dB Impedance: 8Ω Power: RMS/MAX: 100W/300W	\$50,00
	VC-44TI		DIAPHRAGM Ø44.4mm 8 Ohms	\$17,00
	GD-018-B		DRIVER UNIT Voice Coil Ø51.6 Titanium Freq. Resp: 1500-20KHz Sensitivity: 115dB Impedance: 8Ω Power: RMS/MAX: 120W/300W	\$70,00
	GD-018-B DIAPHRAGM		DIAPHRAGM Ø51.6mm 8 Ohms Titanium	\$25,00
	TU-60 DIAPHRAGM		100 W Diaphragm 16 ohms	\$5,00
	TU-60		DRIVER UNIT Power RMS: 100W Power Max: 150W Impedance: 16 Ohm Frequency Range: 200 - 5000Hz	\$34,00
HORN SPEAKER	HS-85		HORN SPEAKER 8" x 5". Power 30W RMS Impedance: 8 Ohms Frequency Response: 500 Hz-5kHz S.P.L. (1W/1m) 105 Db Magnet: Ø 80x15 ABS: material	\$30,00
	YH300T		HORN SPEAKER Input Voltage:100V Freq. Resp: 200-5KHz S.P.L. (1W/1m) : 108 Db Power RMS : 60W Size: 285 x 280 x 285 mm. ABS Plastic	\$70,00
	TH-6		HORN 6" BOŞ	\$20,00
	YASSI		YASSI PLASTİK HORN HOPARLÖR BORUSU BOŞ	\$22,00
	YUVARLAK		YUVARLARK PLASTİK HORN HOPARLÖR BORUSU BOŞ	\$22,00
	ALÜMİNYUM		ALÜMİNYUM HORN HOPARLÖR BORUSU BOŞ	\$22,00
	Q-215		XLR Erkek	\$2,00
Q-214		XLR Dişi	\$2,00	
L-1		Mono Çivi Jak	\$2,00	

JAKLAR	L-29		Mono Çivi Jak	\$2,00
	L-1 S		6.3 mm Stereo Çivi Jak	\$2,00
	L-77		Mono çivi L JAK	\$3,00
	L-337		3.5 mm Stereo	\$3,00
	L-97		6.3 mm Uzatma	\$3,00
	L-334		RCA	\$2,50
	L-165		6.3 mm Uzatma	\$3,00
	Q-246 (4P)		Speakon Konnektör	\$3,00
	Q-311		Speakon Konnektör	\$5,00
	Q-308		Speakon Konnektör	\$2,00
	Q-98		Şase Dişi	\$2,50
	L-95		Çivi Şase	\$2,50
STAGE BOX	SB 4		4 KANAL STAGE BOX 4 Kanal Kablo kilitleti Standart XLR Soketler için boş konnektör kutusu	\$25,00
	SB 8		8 KANAL STAGE BOX 8 Kanal Kablo kilitleti Standart XLR soketler için boş konnektör kutusu	\$35,00
	SB 16		16 KANAL STAGE BOX 16 kanal Kablo kilitleti Standart XLR soketler için boş konnektör kutusu	\$45,00
	SB 24		24 KANAL STAGE BOX 24 Kanal Kablo kilitleti Standart XLR soketler için boş konnektör kutusu	\$55,00
AKSESUARLAR	CS-14		5W 100V TRANSFORMER	\$4,00
	X-010		PORTATİF ÇANTA ANFI YEDEK TELSİZ YAKA VEYA EL MİKROFONU	\$50,00
























FİYATLARIMIZA KDV DAHİL DEĞİLDİR.

SERİ	MODEL	GÖRSEL	AÇIKLAMA	FİYAT
100 V PA SİSTEMİ	POWERED MIXER			
	ROXY PM 2500		2x250W 10-CHANNEL POWERED MIXER 250W + 250W / 4 ohms amplifier Main L & R or mono / monitor (Bridge mono, 500W / 8 ohms) 32/40-bit digital stereo Multi-effect processor ve 100 program, 10-band graphic equalizer	\$700,00
	T-60 USB		Rated Power Output: 60W / 100W Speaker Outputs: 70V, 100V & 4~16Ω Frequency Response: 50Hz~16KHz (+1dB, -3dB) S/N Ratio: MIC 1,2,3: 66dB, AUX 1,2: 80dB	\$400,00
	T-240		Rated Power Output: 240W / 400W Speaker Outputs: 70V, 100V & 4~16Ω Frequency Response: 50Hz~20KHz (+1dB, ±3dB) S/N Ratio: MIC 1, 2, 3: 66dB, AUX 1, 2: 80dB	\$730,00
	TI-120		Rated Power Output: 120W / 200W Speaker Outputs: 70V, 100V & 4~16Ω Frequency Response: 50Hz~16KHz (+1dB, -3dB) S/N Ratio: MIC 1, 2, 3 66dB, AUX 1, 2: 80dB	\$500,00
	TI-120 USB		Rated Power Output: 120W / 200W Speaker Outputs: 70V, 100V & 4~16Ω Frequency Response: 50Hz~20KHz (+1dB, ±3dB) S/N Ratio: MIC 1, 2, 3 66dB, AUX 1, 2: 80dB	\$570,00
	TI-240		Rated Power Output: 240W / 400W Speaker Outputs: 70V, 100V & 4~16Ω Frequency Response: 50Hz~16KHz (+1dB, -3dB) S/N Ratio: MIC 1, 2, 3 66dB, AUX 1, 2: 80dB	\$800,00
	TI-240S		Amplifier Section: (4ΩLoad Output) Speaker Zone: 1~5 Output 25W Rated Output Power: 240W / 320W Frequency Response (±3dB): 50Hz~16KHz Phantom Power: + 48V	\$1.100,00
	TI-350S		Amplifier Section (4ΩLoad Output) Speaker Zone 1~5 Output 25W Rated Output Power 350W / 500W Frequency Response (±3dB) 50Hz~16KHz Phantom Power + 48V	\$1.300,00
	T-6217		Input: 10BGM amp inputs, 10 EMC amp inputs: 70V or 100V, COM Output:10 channel speaker outputs, each channel max output 500W Power Supply : 10V/60Hz or ~230V/50Hz	\$620,00
	T-6204		Power Supply: 110V/60Hz or ~230V/50Hz Power Consum: 30W Dimension: 484x303x88mm	\$380,00
	T-6241		Power Input : 100V constant voltage. Two screw-nut terminals Audio Output : 1.2V, 1V, 0.7V, 6.35mm jacks Output Voltage : DC24V/1A, 230V/50Hz/2A Frequency Response : 80Hz~16KHz(±2dB) Power Supply : 110V/60Hz or ~230V/50Hz	\$480,00
	T-1S240		Rated Power Output: 240W / 400W Speaker Outputs: 70V, 100V & 4~16Ω Frequency Response: 50Hz~16KHz(+1dB, -3dB) S/N Ratio: 90dB	\$780,00
	T-6350		Rated Power Output 350W / 500W Speaker Outputs: 770V, 100V & 4~16Ω Frequency Response: 50Hz~16KHz(+1dB, -3dB) S/N Ratio: 90dB	\$980,00
	T-6500		Rated Power Output: 550W / 720W Speaker Outputs: 770V, 100V & 4~16Ω Frequency Response: 50Hz~16KHz(+1dB, -3dB) S/N Ratio: 90dB	\$1.080,00
	T-6650		Rated Power Output: 650W / 950W Speaker Outputs: 770V, 100V & 4~16Ω Frequency Response: 50Hz~16KHz(+1dB, -3dB) S/N Ratio: 90dB	\$1.180,00
	T-4S120		Rated Power Output: 4x120W Speaker Outputs:70V, 100V & 4~16Ω Frequency Response:50Hz~16KHz(+1dB, -3dB) S/N Ratio: >90dB	\$1.280,00
	T-318		Frequency Response: 50Hz~16KHz, -3dB S/N Ratio: Better than 65dB	\$320,00
	T-672		Rated Power: 20W Line Input:100V Attenuation Per Step: 30dB Finished Color: White Mounting: Flush and Surface	\$32,00
	T-8000		Line1-4 Input: 195mV -2V/10KΩ Line5-7 Input: MIC: 5mV/600Ω, Line: 350mV3/10KΩ Microphone 1: 5mV-280mV/600Ω Tone Control: 100Hz±10dB, 10KHz±10dB Frequency Response: MIC: 80Hz~18KHz(+1/-3dB) Line: 20Hz~20KHz (+1/-3dB) Priority: Mic1, voice alarm, local mic paging, remote zone paging, line 1-8 Weight: 6Kg	\$1.980,00
T-8000A		Frequency Response: 50Hz~18KHz (±2dB) Signal Output: 0.775V/600Ω Mic Input: 5mV/600Ω Power Supply: DC 24V Power Consumption: 5W Weight: 2.5Kg	\$376,00	















MATRIX SYSTEM	T-8000AE		The remote paging console can work together with the matrix to set up a 32 zone paging system. Each matrix could accommodate 4 remote paging consoles which could be distinguished by dipswitch. Each remote paging console is designed for a eight zones paging capacity, while extension keypad may be added to it where more than 8 zones up to 32 zones paging capacity is needed. Maximum 3 extension keypads could be added.	\$200,00
	T-8000C		Serial Communication Speed: 4800bps Serial Communication Distance: Maximum 1Km Communication Port: RJ45 Communication Protocol: RS485 Controls: Volume control Power Supply: DC 24V Power Consumption: 5W Weight: 300g	\$132,00
	NSU-75B		DRIVER UNIT Rms Power:75 W Frequency Range: 150 Hz- 5 KHz Throat Dia.: 19mm dia Nominal Impedance: 16 ohms	\$80,00
DRIVER UNIT	NSU-75B DIAFRAM		75 W Diafram 16 ohms	\$15,00
	PR 138		İŞIKLI KÜRSÜ MİKROFONU Uni-Directional Çıkış Empedansı: 200 OHM, 50 HZ-16 KHZ Frequency Response Sensitivity: -38 dB, 2x1.5V Pil veya 9-52V Phantom Power	\$84,00
	PR-138 GOOSENECK		GOOSENECK MICROPHONE Uni-Directional, Çıkış Empedansı: 200 OHM, 50 HZ-16 KHZ Frequency Response Sensitivity: -38 dB, 2x1.5V Pil veya 9-52V Phantom Power	\$50,00
MASA TIPI KÜRSÜ MİKROFONLARI	DM-220		İŞIKLI KÜRSÜ MİKROFONU Uni-Directional, Çıkış Empedansı: 200 OHM, 50 HZ-16 KHZ Frequency Response Sensitivity: -38 dB, 2x1.5V Pil	\$50,00
	TAKSTAR DMS7AS		DRUM SET 1 x TA-8320 kick drum microphone 1 x TA-8260 small drum microphone 3 x TA-8250 small drum microphone 2 x PCM-5400 condenser microphone 2 x W-50 windscreen 2 x CH-58 microphone clamp 1 x Plastic carrying case with foam inlay	\$420,00
	HS 78		HORN SPEAKER Size: 14.25" x 11.5" x 12.2" Power RMS: 200W Impedance: 50V/70V/120V. S.P.L. (1W/M): 121 Db Frequency Response: 140-16 Hz Magnet: Ø110 x 15 + NeFeB Driver Material: ABS	\$200,00
HORN SPEAKER	G-3T		Woofer: 3" Paper cone Tweeter: 1" Mylar Line Transformer: 2/4/8/12W(100V) Frequency response : 100Hz-18KHz BEYAZ (Adet)	\$60,00
DUVAR HOPARLÖRÜ		PR 4	SPEAKER CABINET Model: Control PR 4 Rms Power: 25W Program Power: 120W Sensitivity: 88dB Frequency Response: 70Hz-18kHz	\$80,00
PLASTİK ŞİŞAH/BEYAZ CONTROL TIPI DUVAR HOPARLÖRÜ		PR 4T	SPEAKER CABINET Model: Control PR 4T Rms Power: 25W Program Power: 120W Sensitivity: 88dB Frequency Response: 70Hz-18kHz	\$95,00
		PR 5T	SPEAKER CABINET Model: Control PR 5T Rms Power: 35W Program Power: 150W Sensitivity: 89dB Frequency Response: 60Hz-18kHz	\$125,00
		PR 6	SPEAKER CABINET Model: Control PR 6 Rms Power: 50W Program Power: 200W Sensitivity: 89dB Frequency Response: 55Hz-20kHz	\$140,00
		PR 6T	SPEAKER CABINET Model: Control PR 6T Rms Power: 50W Program Power: 200W Sensitivity: 89dB Frequency Response: 55Hz-20kHz	\$160,00
		PR 8T	SPEAKER CABINET Model: Control PR 8T Rms Power: 85W Program Power: 250W Sensitivity: 90dB Frequency Response: 45Hz-20kHz	\$260,00
	F 3T		3" ÇİFT YÖNLÜ DUVAR TIPI HOPARLÖR Rms Power: 30W Program Power: 150W Sensitivity: 88dB Frequency Response: 70 HZ-20 kHz	\$150,00
F ŞİŞELİ DUVAR TIPI HOPARLÖR				






TAVAN HOPARLÖRLERİ	CS-5008		TAVAN HOPARLÖRÜ Woofer: 5" Polypropylene, Tweeter: 1" Dome, Line Transformer: 10/15/20W (100V), Frequency Response 70HZ-20KHZ, 89 DB Sensitivity: 89dB	\$40,00
	CS-6508		TAVAN HOPARLÖRÜ Woofer: 6.5" Polypropylene, Tweeter: 1" Dome, Line Transformer: 10/15/20W (100V), Frequency Response 60HZ-20KHZ, Sensitivity: 89dB	\$50,00
	CS-8008		TAVAN HOPARLÖRÜ Woofer: 8" Polypropylene, Tweeter: 1" Dome, Line Transformer: 10/20/30W (100V), Frequency Response 55HZ-20KHZ, Sensitivity: 90dB	\$60,00
	CS-15B		TAVAN HOPARLÖRÜ Model: CS-15B 6" Specification: Input: 100V Power: 100W Max Mounting Hole: 185mm Size: 214x170mm	\$25,00
	CS-13		TAVAN HOPARLÖRÜ Model: CS-13 Size:6.5" Input: 70-100V Power: 150W Max Impedance: 8 ohm OD: 188mm	\$20,00
	CS-24B		TAVAN HOPARLÖRÜ Model: CS-24B-5 Size: 5" (185mm) Input: 100V Power: 100W Max Impedance: 8 ohm	\$14,00
TAVAN HOPARLÖRLERİ	CS-20 3"		TAVAN HOPARLÖRÜ Model: CS-20-S3 3" Power: 75W Max Input: 100V Impedance: 8 ohm Size: A: 115mm B: 91mm C: 90mm	\$20,00
	CS-20 5"		TAVAN HOPARLÖRÜ Model: CS-20-S5 5" Power: 100W Max Input: 100V Size: A: 161mm B: 135mm C: 100mm Impedance: 8 ohm	\$22,00
	S 5T		TAVAN HOPARLÖRÜ Model: S-5T 8"/4" Line Transformer: 10/15/20W (100V) Impedance: 8 OHM	\$90,00
	S 6T		TAVAN HOPARLÖRÜ Model: S-6T 6"/2" Line Transformer:10/15/20W (100V) Impedance: 8 OHM	\$110,00
	S 8T		TAVAN HOPARLÖRÜ Model: S-8T 8" Line Transformer:10/20/30W (100V) Impedance: 8 OHM	\$140,00
	DOLU PLASTİK KABİNELER	BW-1215		15" HALI KAPLI KABİN HOPARLÖR Magnet: 50 Oz Impedance: 8 ohm Tweeter: 7"x14" Sensitivity: 94dB (+/-2dB) Rms Power: 500W
PP-0308			8" PLASTIC SPEAKER CABINET Magnet: 30 Oz Impedance: 8 Ohm Frequency Response: 65 Hz-18 kHz Sensitivity: 92dB (+/-2dB) Rms Power: 100W	\$180,00
PP-0310			10" PLASTIC SPEAKER CABINET Magnet: 40 Oz Impedance: 8 Ohm Frequency Response: 55 Hz-18kHz Sensitivity: 94dB (+/-2dB) Rms Power: 300 W	\$250,00
PP0312			12" PLASTIC SPEAKER CABINET Peak Power Handling: 400 W	\$300,00
PP0315			15" PLASTIC SPEAKER CABINET Peak Power Handling: 500W	\$400,00
PP-0312A			12" ACTIVE SPEAKER CABINET Peak Power Handling: 500W / 1000W Impedance 8 Ohm, Sensitivity: 97 DB Frequency Response 50 HZ-18 KHZ	\$450,00
PP-0315A			15" ACTIVE SPEAKER CABINET Peak Power Handling: 600W / 1200W Impedance 8 Ohm, Sensitivity: 98 DB Frequency Response 45 HZ-18 KHZ	\$550,00
MDQW-12			12" SPEAKER CABINET Subwoofer:12" 50 oz, 8 Ω Horn:8.3" x 8.3" Super driver with Titanium Diaphragm,34.4mm coil Rms power :200w	\$340,00

PLASTİK KABİNELER	MDQW -15		15" SPEAKER CABINET Subwoofer:15" 50 oz, 8 Ω Horn:11.5" x 11.5" Super driver with Titanium diaphragm,44.4mm coil Rms power :300w	\$400,00
	MDQW-215		2x15" SPEAKER CABINET Subwoofer:2 x 15" 60 oz, 8 Ω Horn:11.5" x 11.5" Super driver with Titanium diaphragm,44.4mm coil Rms power :500w	\$650,00
	PP0312		12" BOŞ PLASTİK KABİN	\$110,00
	PP0315		15" BOŞ PLASTİK KABİN	\$140,00
	PA 10		10" 2 WAY SPEAKER CABINET Power: 250W Impedance: 8 Ohm Frekans: 50 HZ-18 KHZ Sensitivity: 96 dB	\$330,00
	PA 12		12" 2 WAY SPEAKER CABINET Power: 400W Impedance: 8 Ohm Frekans: 50 HZ-18 KHZ Sensitivity: 96dB	\$400,00
	PC 12		12" SPEAKER CABINET Power: 500W Max Sensitivity: 97 dB Frequency Response: 50 HZ-18 kHz Impedance: 8 ohm	\$420,00
	PC 15		15" SPEAKER CABINET Power: 500W Max Sensitivity: 97 dB Frequency Response: 50 HZ-18 KHZ Impedance: 8 ohm	\$520,00
	PC 15A		15" ACTIVE SPEAKER CABINET Peak Power Handling: 1000W-500W Impedance: 8 ohm Sensitivity: 98 dB Frequency Response: 45 HZ-18 kHz	\$800,00
	KABİN SEHPALARI	TYS-06N		METAL KABİN SEHPASI 110 cm-180cm Taşıma Kapasitesi: 60Kg
TYW-501			DUVAR ASKI APARATI Taşıma Kapasitesi: 35 Kg	\$30,00
MASA TIPI MİKROFON SEHPASI	TYM-25		MASAÜSTÜ MİKROFON SEHPASI Height: 13cm Base Diameter: φ 8.5cm Weight: 0.65 Kg Pipe Colour: Chrome Base: Cast Iron	\$10,00
	TYM-15		DÖKÜM TABANLI MASA SEHPASI Height Adjustment Range: 24cm-38cm Base Diameter: φ 15 cm Weight: 1 Kg Pipe Colour: Chrome/Black Base: Cast Iron	\$20,00
	TYM-30		DÖKÜM TABANLI SİRALLI MASA SEHPASI Weight: 1 Kg Base Diameter: φ15.5 cm Tube Spec: φ1.5 X 30.5 cm Tube Colour: Chrome Base: Cast Iron	\$20,00
	TYM-19		AKROBAT MİKROFON SEHPASI Height Adjustment Range: 38cm-52cm Base Diameter: φ 17.5 cm Cross Bar Length: 42cm Weight: 1.7 Kg Pipe Colour: Chrome/Black	\$28,00
MİKROFON SEHPALARI	TYM-08C		MİKROFON SEHPASI Height Adjustment Range: 90cm-152cm Base Diameter: φ 23.5 cm Weight: 3.2 Kg Pipe Colour: Chrome/Black Base: Cast Iron	\$38,00
	TYM-52B		AKROBAT MİKROFON SEHPASI Height Adjustment Range: 92cm-158cm Cross Bar Length: 78 cm Weight: 2 Kgs Pipe Colour: Black	\$28,00
	TYM-58B		MİKROFON SEHPASI Height: 50 cm Cross Bar Adjustment Length: 56-86 cm Weight: 2.1 Kgs Pipe Colour: Black	\$28,00

NOTA SEHPASI VE MIXER / KEYBOARD SEHPALARI	TYM-90		NOTA SEHPASI Height Adjustment Range: 68 cm -145 cm Weight: 1.1 Kg Colour: Black	\$22,00
	TYM-93B		NOTA SEHPASI Height Adjustment Range: 68cm-145cm Weight: 3.5 Kg Colour: Black	\$40,00
	TYK-01		MIXER / KEYBOARD SEHPASI Height Adjustment Range: 65 cm -96cm Weight : 2.8 Kg Colour : Black Load Capacity : 50 KGS	\$35,00
	TYK-10 N		ORG SEHPASI Height Adjustment Range: 65 cm - 96 cm Weight : 4.5 Kg Colour : Black Load Capacity : 70 KGS	\$70,00
	TYR-02		MIXER SEHPASI Height: 146 cm Weight: 12 KG Load Capacity: 50 Kg Colour: Black	\$120,00
IŞIK SEHPALARI	TYL-01		IŞIK SEHPASI Height Adjustment Range: 200cm-400cm Width: 300cm Cross Bar Length: 120cm Weight: 16 Kg Load Capacity: 120 Kg Colour: Silver/Black	\$200,00
	TYL-02		IŞIK SEHPASI Height Adjustment Range: 150cm-280cm Cross Bar Length: 120cm Weight: 3.4 Kg Load Capacity: 80 Kg Colour: Silver/Black Aluminium Pipe/Iron Pipe	\$80,00
KABİN AVESUELARLARI	TYA-71		METAL DİPLİK 3.55 X 11 cm	\$5,00
	TYH-32		METAL KULP 220x160mm	\$6,00
	TYH-51		12" PANJUR 12" /30 Cm Hoparlör için Klipsleri ile Beraber	\$5,00
	TYH-51		15" PANJUR 15" /38 Cm Hoparlör için Klipsleri ile Beraber	\$6,00
	TYC-50		TERMİNAL PANEL 135x92x1.0mm Speakon / Jak için	\$3,00
	TYC-67		KOMPLE TERMİNAL PANEL 122x95mm (Dişi Speakon+Jak+ Born Klemensi ile birlikte)	\$8,00
	TYA-05		Telsiz Mikrofon Ayı ABS Material Ø3.5cm	\$3,00
	TYA-02		Telsiz Mikrofon Ayı ABS Material Ø3.5cm	\$4,00
	TYA-09		Mikrofon Ayı Polyurethane/Nylon Ø3 cm	\$2,00
	TYF-15		Air Hole Ø102 x 110 mm	\$1,20
	TYF-31		HORN 4" x 10" Threads: 1 3"/8 -18TP1	\$5,00
	TYF-42		HORN 5" x 15" Threads: 1 3"/8 -18TP1	\$10,00
	TYF-45		HORN 6" x 7" Threads: 1 3"/8 -18TP1	\$5,00
	TYF-53		HORN 7" x 15" Threads: 1 3"/8 -18TP1	\$20,00
	KABLOLAR	BX-3		2*1.5 mm2 Hoparlör Kablosu
MK-6			2*0,22 mm2 Mikrofon Kablosu	\$1,10
BMX-4			4 kanal multicore kablo 4x 2*0,22 mm	\$5,20
BMX-8			8 kanal multicore kablo 8x 2*0,22 mm	\$9,80
BMX-16			16 kanal multicore kablo 16x 2*0,22 mm	\$14,00
BMX-24			24 kanal multicore kablo 24x 2*0,22 mm	\$21,00

MUHTELİF

SERİ	MODEL	GÖRSEL	AÇIKLAMA	FİYAT
TELSİZ MİKROFONLAR	TEK EL		UHF 550-610 MHz 16 Kanal PLL Kontrollü LCD Dijital Ekran 1xLCD Ekranlı El Mikrofonu Ses Frekansı 50Hz-15kHz 2x1,5V AA Pili (El Mikrofonu)	\$115,00
	TEK YAKA		UHF 550-610 MHz 16 Kanal PLL Kontrollü LCD Dijital Ekran 1xLCD Ekranlı Bel Cihazı+1xYaka Ses Frekansı 50Hz-15kHz 2x1,5V AA Pili	\$125,00
	ÇİFT EL		UHF 550-610 MHz 2x16 Kanal PLL Kontrollü LCD Dijital Ekran 2xLCD Ekranlı El Mikrofonu Ses Frekansı 50Hz-15kHz 2x1,5V AA Pili (El Mikrofonu)	\$150,00
	EL+YAKA		UHF 550-610 MHz 2x16 Kanal PLL Kontrollü LCD Dijital Ekran 1xLCD Ekranlı El Mikrofonu+1xBel Cihazı+1xYaka Mikrofonu Ses Frekansı 50Hz-15kHz 2x1,5V AA Pili (El Mikrofonu ve Bel Cihazı)	\$160,00
	ÇİFT YAKA		UHF 550-610 MHz 2x16 Kanal PLL Kontrollü LCD Dijital Ekran 2xBel Cihazı+2xYaka Mikrofonu Ses Frekansı 50Hz-15kHz 2x1,5V AA Pili (Bel Cihazı)	\$170,00
	HEADSET		Ten Renk Head Set Mikrofon	\$40,00
MEGAFONLAR	MEGAFON		25W MİNİ MELODİLİ MEGAFON 240sn Ses Kayıt yapabileme USB'den Şarj Edilebilir 3,7VDC Batarya Dahili Melodili, Volume kontrol ayarlı 150x250 mm	\$35,00
	MEGAFON		30W MİNİ MELODİLİ MEGAFON Bluetooth ile bağlantı 300sn Ses Kayıt yapabileme USB ve Adaptörle Şarj Edilebilir 3,7VDC Batarya, Batarya Seviye Göstergesi, USB, TF kart, Dahili Melodili Siren Volume kontrol ayarlı 130x195 mm	\$50,00
	MEGAFON		50W MIKE MİKROFONLU MEGAFON 120sn Ses Kayıt Yapabileme Şarj Edilebilir Batarya yada 3XC Tipi Pille Çalışma USB, TF kart, 3,5mm AUX giriş, Siren, Volume kontrol ayarlı 205x340 mm	\$70,00
	MEGAFON		100W MIKE MİKROFONLU MEGAFON Bluetooth ile bağlantı 12V Adaptör Girişi, Şarj Edilebilir Batarya yada 8XC Tipi Pille Çalışma, USB, TF kart, 3,5mm AUX giriş, Siren, Volume kontrol ayarlı 215x380 mm	\$120,00
	AKILLI OKUL SAATLERİ	TKS-209R		Dijital grafik ekranda menü ile kolay kullanım ve programlama Hergün için 24 ayrı ders programı ve 5 farklı toplanma programı Okuma saati ve blok ders girebilme imkanı Seçilen zil sesinin sonuna sesli öğrenci, öğretmen ikazı ilave edebilme MP3 formatında dahili ve USB girişinden harici sınırsız zil sesleri Usb girişinden tennefüslerde müzik dinleme Uzaktan kumanda ile İstiklal marşı okutabilme Deprem, yangın ve acil durum sivil savunma sirenleri ve 10 Kasım sireni Kendine bağlı Amplifikatörü otomatik Açma/Kapama ve uygun sinyal çıkışı Dahili monitör hoparlör ile ön dinleme Duvar montajına uygun AC giriş 220V 50Hz
TKS-209A			Dijital grafik ekranda menü ile kolay kullanım ve programlama Hergün 24 ayrı ders programı ve 5 farklı toplanma programı Okuma saati ve blok ders girebilme imkanı Seçilen zil sesinin sonuna sesli öğrenci, öğretmen ikazı ilavesi MP3 formatında dahili ve USB girişinden harici sınırsız zil sesleri USB girişinden tennefüslerde müzik dinleme Uzaktan kumanda ile İstiklal marşı okutabilme Deprem, yangın, acil durum sivil savunma ve 10 Kasım sireni Kendini ve kendine bağlı Amplifikatörü otomatik Açma/Kapama ve uygun sinyal çıkışı Dahili monitör hoparlör ile ön dinleme 2x150W Amplifikatör çıkış gücü	\$840,00
TKS-216R			İç ve dış sesleriyle okul içindeki ve dışındaki honorarlerin seslerini bağımsız Dijital grafik ekranda menü ile kolay kullanım ve programlama Hergün için 50 ayrı ders programı ve 5 farklı toplanma programı 50 Ad. Dahili MP3 formatında zil sesi USB'den tennefüslerde müzik çalma USB'den Flaş belleğe /Flaş bellekten Ders Programı yedekleme PC'den ders programını düzenleme Her ders için ayrı ayrı giriş-çıkış ve uyarı zilini ve süresini ayarlayabilme Seçilen zil sesinin sonuna sesli öğrenci, öğretmen ikazı ilave edebilme Menü üzerinden İstiklal marşı başlatabilme Kendine bağlı Amplifikatörü otomatik Açma/Kapama ve uygun sinyal çıkışı Dahili monitör hoparlör ile ön dinleme 19" rack kabine uygun	\$310,00
TKS-207R			Dijital grafik ekranda menü ile kolay kullanım ve programlama 6 Adet zil sesi Hergün için 24 ayrı ders programı Tennefüslerde ara müziği dinlemek için MP3 çalar Ders giriş çıkış ve öğretmen zilini ve süresini ayrı ayrı seçebilme 10 yıl saat pil ömrü ve 100 yıllık takvim Kendine bağlı Amplifikatörü otomatik Açma/Kapama ve uygun sinyal çıkışı İstendiği zaman elle zil çaldırma AC giriş 220V 50Hz 19" rack kabine uygun Ölçüler (mm): 440x205x110 Ağırlık: 3 kg Kullanım Yerleri: Okullar Dershaneler Fabrikalar Halı sahalarda alanlarda	\$220,00

PROGRAMI EZAN SAATLERİ	TKS-207D		Dijital grafik ekranda menü ile kolay kullanım ve programlama 6 adet zil sesi Hergün için 24 ayrı ders programı Teneffüslerde ara müziği dinlemek için MP3 çalar Ders giriş çıkış ve öğretmen zilini ve süresini ayrı ayrı seçebilme 10 yıl saat pili ömrü ve 100 yıllık takvim Kendine bağlı Amplifikatörü otomatik Açma/Kapama ve uygun sinyal çıkışı Çan'lı zil sesi için AC 220V anahtarlama İstendiği zaman elle zil çaldırma AC giriş 220V 50Hz Plastik yapıda duvar tipi montaj aparatlı Ölçüler (mm): 173x153x62 Ağırlık: 800 gr Hergün için 48 adet program girilebilir Her program için ayrı melodi veya sözlü bildirim İş başlangıçlarında İşçi Sağlığı ve Güvenliği ile ilgili uyan anonsları Gün başlangıcında veya hafta başlangıcında BEREKET Duası Flaş bellekten mesaide-molada veya her ikisinde müzik dinleyebilme Programı flaş belleğe aktarma, programlama, flaş bellek ile güncelleme Yangın santralinden alınan kuru kontak bağlantısı ile yangın alarmı verebilme Olağanüstü durumlarda ve 10 Kasım'da siren çalabilme 3W dahilli monitör ile ön dinleme Kendine bağlı Amplifikatör veya Telsiz vericisini otomatik Açma/Kapama ve Sinyal çıkışı Amplifikatör açma süresini ayarlanabilir	\$180,00
	TKS-217R		Her program için ayrı melodi veya sözlü bildirim İş başlangıçlarında İşçi Sağlığı ve Güvenliği ile ilgili uyan anonsları Gün başlangıcında veya hafta başlangıcında BEREKET Duası Flaş bellekten mesaide-molada veya her ikisinde müzik dinleyebilme Programı flaş belleğe aktarma, programlama, flaş bellek ile güncelleme Yangın santralinden alınan kuru kontak bağlantısı ile yangın alarmı verebilme Olağanüstü durumlarda ve 10 Kasım'da siren çalabilme 3W dahilli monitör ile ön dinleme Kendine bağlı Amplifikatör veya Telsiz vericisini otomatik Açma/Kapama ve Sinyal çıkışı Amplifikatör açma süresini ayarlanabilir	\$400,00
	TKS-014		81 il ve KKTC'ye uyumlu (İlçe ve Köyler dahil isteğe bağlı tüm ülkelere uyumlu) Her vakit ezan kendi makamında ve sela mp3 kalitesinde okunur Cum'a öncesi otomatik sela, Perşembe akşamı isteğe bağlı sela okuma Arzu edilen vakitler kapatılabilir, her vakte temkin ayarı yapılabilir Ramazan ayında imsak öncesi Sela, İmsak vakti ezan okuma 10 yıl saat pil ömrü 100 yıllık takvim Elle kontrol Ezan ve Sela okutma USB'den yazılım güncelleme Kendine bağlı Amplifikatörü otomatik Açıp/Kapatma ve uygun sinyal çıkışı 3W dahilli monitör AC giriş 220V 50Hz Ölçüler (mm): 225x190x60 plastik duvar tipi kasa	\$310,00
	TKS-08R		81 il ve KKTC'ye uyumlu (İlçe ve Köyler dahil isteğe bağlı tüm ülkelere uyumlu) Her vakit ezan kendi makamında ve sela mp3 kalitesinde okunur Cum'a öncesi otomatik sela, Perşembe akşamı isteğe bağlı sela okuma Arzu edilen vakitler kapatılabilir, her vakte temkin ayarı yapılabilir Ramazan ayında imsak öncesi Sela, İmsak vakti ezan okuma 3 farklı seste Ezan ve Sela seçimi 10 yıl saat pil ömrü 100 yıllık takvim Elle kontrol Ezan ve Sela okutma USB'den yazılım güncelleme Kendine bağlı Amplifikatörü otomatik Açıp/Kapatma ve uygun sinyal çıkışı 3W dahilli monitör hoparlör AC giriş 220V 50Hz	\$445,00
	TKS-08A		19" kabin montajı 81 il ve KKTC'ye uyumlu (İlçe ve Köyler dahil isteğe bağlı tüm ülkelere uyumlu) Her vakit ezan kendi makamında ve sela mp3 kalitesinde okunur Cum'a öncesi otomatik sela, Perşembe akşamı isteğe bağlı sela okuma Arzu edilen vakitler kapatılabilir, her vakte temkin ayarı yapılabilir Ramazan ayında imsak öncesi Sela, İmsak vakti ezan okuma 3 farklı seste Ezan ve Sela seçimi 10 yıl saat pil ömrü 100 yıllık takvim Elle kontrol Ezan ve Sela okutma USB'den yazılım güncelleme Kendine bağlı Amplifikatörü otomatik Açıp/Kapatma ve uygun sinyal çıkışı 1 mikrofon (2mV), 1 line (30mV) ve 1 ezan kontrol kanalı 3W dahilli monitör hoparlör AC giriş 220V 50Hz	\$735,00
	42U			\$500,00
32U	32U 19" 600x600 CAM KAPAKLI KİLİTLİ METAL RACK KABİNET		\$400,00	
26U	26U 19" 600x600 CAM KAPAKLI KİLİTLİ METAL RACK KABİNET		\$280,00	
20U	20U 19" 600x600 CAM KAPAKLI KİLİTLİ METAL RACK KABİNET		\$210,00	
16U	16U 19" 600x600 CAM KAPAKLI KİLİTLİ METAL RACK KABİNET		\$170,00	
12U	12U 19" 600x600 CAM KAPAKLI KİLİTLİ METAL RACK KABİNET		\$130,00	
9U	9U 19" DUVAR TİPİ CAM KAPAKLI KİLİTLİ METAL RACK KABİNET		\$80,00	
7U	7U 19" DUVAR TİPİ CAM KAPAKLI KİLİTLİ METAL RACK KABİNET		\$65,00	
RAF	19" METAL RAF		\$20,00	
2'Lİ FAN	2'Lİ TERMOSTATLI FAN ÜNİTESİ		\$50,00	
4'LÜ FAN	4'LÜ TERMOSTATLI FAN ÜNİTESİ		\$75,00	
TEKERLEK	4'LÜ 2 AD FRENLİ 2 AD SERBEST TEKERLEK TAKIMI		\$40,00	
6'LI GRUP PRİZ	6'LI SİGORTALI GRUP PRİZ		\$40,00	

FİYATLARIMIZA KDV DAHİL DEĞİLDİR.



STANDART CASELER			
KAPAKSIZ RACK CASE 19"		2U 152\$ 4U 174\$ 6U 203\$ 8U 220\$ 10U 248\$ 12U 265\$	14U 288\$ 16U 310\$ 18U 337\$ 20U 342\$ 22U 358\$ 24U 385\$
2 KAPAKLI RACK CASE 19"		2U 242\$ 4U 270\$ 6U 292\$ 8U 315\$ 10U 332\$ 12U 354\$	14U 377\$ 16U 394\$ 18U 416\$ 20U 433\$ 22U 461\$ 24U 478\$
3 KAPAKLI SABİT RAY RACK CASE		8U 356\$ 10U 372\$ 12U 389\$	14U 506\$ 16U 523\$ 18U 539\$
METAL RACK CASE		12U 150\$ 20U 200\$ 28U 250\$	
TEKERLEK MODÜLÜ		85\$	
ÇEKMECELER		1U 100\$ 2U 130\$ 3U 150\$ 4U 170\$	
RAF / TAVALAR		1U 26\$ 2U 34\$ 3U 50\$	
PANEL		1U 20\$ 2U 24\$ 3U 28\$	
PIONEER DJ CASE	2 Turntable ve 1 Mixerden oluşan DJ Setup için case	106x48x20	\$478,00
KABLO KUTUSU	Üstten kapaklı, tekerlekli, içi halı kaplı kablo yada ekipman kutusu	102x52x61	\$484,00
REJİ MONİTÖR	Reji Monitörü için çift kapaklı özel kutu	27x49x30	\$354,00
PROJEKSİYON KUTUSU	Projeksiyon cihazı kutusu	38x22x46	\$281,00
100 BÖLME CASE	100 Bölmeli alıcı yada kulaklık kutusu	75x55x19	\$607,00
LCD TV 42 INCH	42" Ekranlı LCD televizyon için kutu	108x16x70	\$444,00
ROBOT KUTUSU K	Motorize ışık, floodlight yada robot kutusu. Çift cihaz taşıy	94x51x57	\$708,00
ROBOT KUTUSU B	Büyük boy motorize ışık, floodlight yada robot kutusu. Çift cihaz taşıy	102x63x70	\$776,00
MİKROFON KUTUSU	12 Mikrofon alabilen üstten kapaklı, sünger dolgulu, iki bölmeli kutu	46x33x26	\$174,00
YAMAHA MG 24/14	Mixer kutusu	89x63x24.5	\$382,00

YAMAHA MG 32/14	Mixer kutusu	110x63x24.5	\$411,00
YAMAHA EMX5000	Mixer kutusu	76x61x28	\$366,00
BEHRINGER PMP3000	Mixer kutusu	55x53x24	\$337,00
BEHRINGER XENYX1832	Mixer kutusu	49x44x22	\$326,00
BEHRINGER SL3242	Mixer kutusu	97x48x22	\$366,00
DYNACORD PM1000	Mixer kutusu	57x57x30	\$354,00
DYNACORD PM1600	Mixer kutusu	63x54x25	\$343,00
SOUNDCRAFT LX7 32CH	Mixer kutusu	110x63x26	\$411,00
PHONIC K16	Mixer kutusu	75x59x34	\$366,00
ALLEN&HEATH PA20CP	Mixer kutusu	79x59x30	\$371,00
ALLEN&HEATH PA28	Mixer kutusu	102x63x26	\$394,00
ALLEN&HEATH GL2400/24	Mixer kutusu	101x63x27	\$394,00
ALLEN&HEATH GL2400/32	Mixer kutusu	110x63x26	\$411,00

1U = 4,45 cm olarak hesaplanacaktır.
Mixer kutuları ve özel amaçlı kutularda bir ölçüsü 110 cm.yi geçen modeller için fiyat alınız
Adetli alımlarınız için özel fiyat sorunuz
Fiyatlarımızda %18 KDV hariçtir



DCA

SERİ	MODEL	GÖRSEL	AÇIKLAMA	FİYAT
FRESNEL SPOTLAR	PC-1000		Stage 1000 PC Antialo tiyatro spotu, Lamp 650/1000 watt, soket GX 9,5, beam divergence 13°- 64° (Ampul hariç)	\$240,00
	FR-1000		Stage 1000 Fresnel spot, Lamp 650/1000 watt, soket GX 9,5, beam divergence 16°- 53° (Ampul hariç)	\$240,00
	AF-1000		DKP saclan üretilmektedir. Halojen ampul kullanılır, geniş ve huzmeli ışık verirler. Ampul sıcaklığını kolaylıkla atacak şekilde dizayn edilmiş, 3X1.5 mm2 adet silikon kablo ile beslenen, 220X245 mm adet renk çerçevesi bulunan, fosfat kaplandıktan sonra, güneş ışıklarına dayanıklı polyester statik toz boya ile boyanan siyah renkte üretilen, diğer renk seçeneklerinde sipariş edilebilen profesyonel sahne ışık gerecidir. Power 1000 watt 220/50V	\$170,00
	AF-3000		DKP saclan üretilmektedir. Halojen ampul kullanılır, geniş ve huzmeli ışık verirler. Ampul sıcaklığını kolaylıkla atacak şekilde dizayn edilmiş, 3(3X1,5mm2) adet silikon kablo ile beslenen, 3(220X245mm) adet renk çerçevesi bulunan, fosfat kaplandıktan sonra, güneş ışıklarına dayanıklı polyester statik toz boya ile boyanan siyah renkte üretilen, diğer renk seçeneklerinde sipariş edilebilen profesyonel sahne ışık gerecidir. Power 3x500/1000 watt 220/50V	\$400,00
	BD-01		Sahnenizdeki ışığı nereye düşüğünü kontrol etmek için kullanılabilen 21cm standart reflektör için elinchrom barndoor setidir. Işık noktasının boyutu yaprakların açılması ve ışığın öznenen uzaklığı ile belirlenebilir.	\$80,00
	FR-750		Profile spot ,Lamp 575 / 600 / 750W HPL .Socket G 9.5.Colour temperature 3200K, life 300 hours (Ampul hariç) 20° and 40°	\$700,00
TRUSS AYIĞI	TA300		TA180 Truss lift -Max Load:300kg Min Load:20kg Insertion:35mm Height displayed:5.5m max Base thomann displayed :2x2 m Folded height:1.78m Folded base:0.5x0.5 m Weight:105kg TRUSS BAĞLANTI APARATI DAHİLDİR.	\$2.604,00
CINEMA CABINET	DCA CSC6		6" CINEMA SURROUND CABINET Freq. Response: 40Hz.-20KHz Impedance: 8 ohms Cont. Pink Noise: 100W Cont. Program: 200W Sensitivity 1W/1m: 90 dB Crossover Freq.: 2700 Hz	\$205,00
	DCA CSC8		8" CINEMA SURROUND CABINET Freq. Response: 40Hz.-18KHz Impedance: 8 ohms Cont. Pink Noise: 150W Cont. Program: 300W Sensitivity 1W/1m: 92 dB Crossover Freq.: 2500 Hz	\$227,00
	DCA CSC10		10" CINEMA SURROUND CABINET Freq. Response: 40Hz.-18KHz Impedance: 8 ohms Cont. Pink Noise: 200W Cont. Program: 400W Sensitivity 1W/1m: 95 dB Crossover Freq.: 2400 Hz	\$265,00